## LISTING OF THE CLAIMS

The following listing, if entered, replaces all prior versions of the claims in the present application.

1. **(Currently Amended)** A method comprising:

receiving a first multicast routing protocol (MRP) message **at a rendezvous point (RP) router**, wherein the first MRP message is a request to join a multicast group;

translating the first MRP message into a second MRP message, wherein the second MRP message is a request to join the multicast group of receivers to which data is being provided by a specific source**, and the translating is performed by the rendezvous point (RP) router**.

**2. Cancelled.**

**3. Cancelled.**

4. **(Currently Amended)** The method of claim **[[2]]1** wherein the RP router is contained in a first network that operates according to a first multicast routing protocol, wherein the specific source is contained in a second network that operates according to a second multicast routing operating protocol, and wherein the first and second multicast routing operating protocols are different from each other.

5. **(Currently Amended)** The method of claim **[[2]]1**wherein the first network contains a plurality of routers including the RP router, wherein the second network contains a plurality of routers, and wherein the RP router is positioned within the first network such that data transmitted by RP router to the second network does not pass through another router of the first network.

6. (Original) The method of claim 5 further comprising:
the RP router transmitting the second MRP message to the second network;
creating a first communication path between the specific source and a receiver in the first network after the router transmits the second MRP message, wherein the first communication path does not include the RP router;
transmitting data from the specific source to the receiver via the first communication path.

7. (Original) The method of claim 6 further comprising:
creating a second communication path between the specific source and the receiver after data is transmitted from the specific source to the receiver via the first communication path, wherein the RP router is not included in the second communication path;
transmitting more data from the specific source to the receiver via the second communication path.

8. (Original) The method of claim 1 wherein translating comprises:
inputting first data into a look-up table (LUT), wherein the first data comprises an identity of the multicast group of receivers;
the LUT outputting second data in response to inputting first data, wherein the second data comprises an identity of the specific source.

9. (Original) The method of claim 8 wherein the LUT can be stored in memory of the device that translates the first MRP message into the second MRP message or stored in remote memory accessible using a communication protocol.

10. **(Currently Amended)** The method of claim **[[3]]1** wherein the router is contained in a sparse mode (SM) communication network and wherein the second MRP message is configured for subsequent transmission to a source specific mode (SSM) communication network.

11. **(Currently Amended)** An apparatus comprising:

a processor;

a first memory coupled to the processor, wherein the first memory stores instructions executable by the processor;

wherein the processor implements a method in response to executing the instructions, the method comprising:

translating a first MRP message **which has been received by a rendezvous point (RP) router** into a second MRP message, wherein the first MRP message is a request to join a multicast group of receivers, ~~and~~ wherein the second MRP message is a request to join the multicast group of receivers to which data is being provided by a specific source**, and wherein the translating is performed by the RP router**.

12. **(Currently Amended)** An apparatus comprising:

means for receiving a first multicast routing protocol (MRP) message **by a rendezvous point (RP) router**, wherein the first MRP message is a request to join a multicast group of receivers;

means for translating the first MRP message into a second MRP message, wherein the second MRP message is a request to join the multicast group of receivers to which data is being provided by a specific source**, and the translating is done by the RP router.**

13. **(Currently Amended)** A memory medium storing instructions readable and executable by a **rendezvous point (RP)** router comprising a processor, wherein the router performs a method in response to executing the instructions, the method comprising:

translating a first MRP message into a second MRP message, wherein the first MRP message is a request to join a multicast group of receivers, and wherein the second MRP message is a request to join the multicast group of receivers to which data is being provided by a specific source.

**14. Cancelled.**

15. **(Currently Amended)** The memory medium of claim **[[14]]13** wherein the RP router is contained in a first network that operates according to a first multicast routing protocol, wherein the specific source is contained in a second network that operates according to a second multicast routing operating protocol, and wherein the first and second multicast routing operating protocols are different from each other.

16. **(Currently Amended)** The memory medium of claim **[[14]]13** wherein the first network contains a plurality of routers including the RP router, wherein the second network contains a plurality of routers, and wherein the RP router is positioned within the first network such that data transmitted by RP router to the second network does not pass through another router of the first network.

17. (Original) The memory medium of claim 16 wherein the method further comprises:

the RP router transmitting the second MRP message to the second network;

creating a first communication path between the specific source and a receiver in the first network after the RP router transmits the second MRP message, wherein the first communication path does not include the RP router;

transmitting data from the specific source to the receiver via the first communication path.

18. (Original) The memory medium of claim 17 wherein the method further comprises:

creating a second communication path between the specific source and the receiver after data is transmitted from the specific source to the receiver via the first communication path, wherein the RP router is not included in the second communication path;

transmitting more data from the specific source to the receiver via the second communication path.

19. (Original) The memory medium of claim 13 wherein translating comprises:

inputting first data into a look-up table (LUT), wherein the first data comprises an identity of the multicast group of receivers;

the LUT outputting second data in response to inputting first data, wherein the second data comprises an identity of the specific source.

20. **(Currently Amended)** The memory medium of claim **[[14]]**<u>13</u> wherein the router is contained in a sparse mode (SM) communication network and wherein the second MRP message is configured for subsequent transmission to a source specific mode (SSM) communication network.